

# AT-KDH

Tilting table



Product data sheet  
AT-KDH  
01/22 PR70092

## Our know-how - your advantage

Working tables with optional tilting, turning and lifting device – available with different table surfaces.

- ergonomically adjustable position for each working field
- steplessly pneumatic lift by 400 mm
- vertical table inclination/roller conveyor, adjustable from 7° to 10°
- horizontal and vertical telescopic support surface
- Lateral cut-out for better accessibility
- Table support, steplessly tiltable from vertical to horizontal
- Table support with 360° turning unit, without resetting, including locking brake for elements

### Options

- roller conveyor support with two different roller lengths, selectable
- roller conveyor extension
- mobile version
- various table surfaces: Silicone, felt, mushroom (hard/soft) and brush

## Technical information



### AT-KDH 14/19

Table width 1400 mm  
Table height 1900 mm

vertical transfer height  
230 mm - 630 mm




### AT-KDH 18-23/20-27 (telescopic table support)

Table width 1800 mm - 2300 mm  
Table height 2000 mm - 2700 mm

vertical transfer height  
230 mm - 630 mm


(roller conveyor firmly mounted  
to 230 mm transfer height)

Machining details:  
min. size



AT-KDH 14/19  
a = 1400 mm  
b = 1900 mm

AT-KDH 18-23/20-27  
a = 2300 mm  
b = 2700 mm



AT-KDH 14/19  
a = ca. 1410 mm  
b = ca. 1970 mm  
c = ca. 945 mm  
d = ca. 2100 mm

AT-KDH 18-23/20-27  
a = ca. 1830 mm  
b = ca. 1970 mm  
c = ca. 945 mm  
d = ca. 2100 mm



AT-KDH 14/19 212 kgs  
AT-KDH 18-23/20-27 360 kgs



6 - 8 bar



70 l per cycle

load capacity

max. 150 kgs

Technical data are valid for basic machine without options. Size according to layout.

Urban GmbH & Co. Maschinenbau KG

Dornierstraße 5  
DE - 87700 Memmingen  
Tel.: +49 (0) 8331 858 - 0  
E-Mail: urban@u-r-b-a-n.com  
www.u-r-b-a-n.com

Subject to errors and modifications